

RUBIA XT

15W-40



Multigrade oil for diesel engine

UTILISATION

- Developed for all Diesel engines, turbocharged or not, in severe service conditions in all seasons.
- Suited for extended drain intervals (up to 30 000 km according to manufacturers).

PERFORMANCES

Specifications

ACEA E2
API CF-4/SJ

OEMS' approvals

MERCEDES MB-Approval 228.1
MAN 271
VOLVO VDS
MIL-L 2104 E

CUSTOMER BENEFITS

Performances techniques

- Multigrade
- Very high viscosity index
- Excellent viscosity stability in operation
- Excellent detergency level
- High dispersancy level
- Excellent antiwear and anticorrosion properties
- Very good anti oxydant, antirust and antifoam properties.

CHARACTERISTICS

	Units	SAE grade 15W-40
Volumetric mass at 15°C	kg/m ³	887
Viscosity at 100°C	mm ² /s	13.9
Viscosity index	-	131
Flash Point	°C	>200
Pour point	°C	-30
T.B.N	mgKOH/g	9.2

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS

Le SPAZIO
562 Avenue du Parc de l'île
92029 - NANTERRE CEDEX

RUBIA XT 15W-40
May 2009
N° MPR 05/09



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.